

Karta katalogowa rodziny produktów LUMILUX T5 HE

Światłówki liniowe o średnicy 16 mm, o wysokiej skuteczności, z trzonkiem G5



- Public buildings Offices Shops Supermarkets and department stores Industry Outdoor applications only in suitable luminaires

- Good economy and efficiency Up to 20 % more economical than LUMILUX T8 Up to 50 % smaller volume than comparable T8 lamps
- Caratteristiche prodotto Efficienza luminosa: fino a 104 lm/W Ottimo mantenimento del flusso luminoso: 90% per tutta la durata della lampada Lunga durata media: fino a 24.000 ore (con alimentatore elettronico QUICKTRONIC) Buon classe di resa cromatica: 1B (Ra: 80...89) Dimmerabile Vantaggi prodotto Buona economicità ed efficienza Fino al 20% più conveniente rispetto alla LUMILUX T8 Volume fino al 50% minore rispetto alle lampade standard comparabili Aree applicative Edifici pubblici Uffici Negozi Supermercati e grandi magazzini Industria Applicazioni outdoor sono negli apparecchi adatti Garanzia di sistema Garanzia OSRAM System+ in combinazione con gli alimentatori elettronici OSRAM Consigli per la sicurezza In caso di rottura della lampada consultare:
"www.ledvance.com/brokenlamp" Referenze/links Vedere la scheda tecnica dettagliata per maggiori informazioni di sicurezza. "www.ledvance.com/system-guarantee"



Dane techniczne

	Dane elektryczne	Dane fotometryczne	Wymiary i waga			Dodatkowe dane produktu	
Opis produktu	ZLDV_Nominal current [AGGR]	ZLDV_Light color (designation) [AGGR]	ZLDV_Tube diameter [AGGR]	ZLDV_Product weight [AGGR]	ZLDV_Overall length [AGGR]	ZLDV_Product remark [AGGR]	Produkt zastępczy EAN
HE 14 W/840 ¹⁾	0.17 A A	LUMILUX Cool White	16 mm	44.26 g	563.20 mm	Suitable for ECG operation only Lamp designed for internal luminaire temperatures of 30...40 °C; optimum luminous flux achieved at 35 °C	4050300464688
HE 21 W/840 ¹⁾	0.17 A A	LUMILUX Cool White	16 mm	70.92 g	863.20 mm	Suitable for ECG operation only Lamp designed for internal luminaire temperatures of 30...40 °C; optimum luminous flux achieved at 35 °C	4050300464701
HE 28 W/840 ¹⁾	0.17 A A	LUMILUX Cool White	16 mm	88.02 g	1163.20 mm	Suitable for ECG operation only Lamp designed for internal luminaire temperatures of 30...40 °C; optimum luminous flux achieved at 35 °C	4050300464725

Karta katalogowa rodziny produktów

	Dane elektryczne	Dane fotometryczne	Wymiary i waga			Dodatkowe dane produktu	
Opis produktu	ZLDV_Nominal current [AGGR]	ZLDV_Light color (designation) [AGGR]	ZLDV_Tube diameter [AGGR]	ZLDV_Product weight [AGGR]	ZLDV_Overall length [AGGR]	ZLDV_Product remark [AGGR]	Produkt zastępczy EAN
HE 28 W/865 ¹⁾	0.17 A A	LUMILUX Cool Daylight	16 mm	88.02 g	1163.20 mm	Suitable for ECG operation only Lamp designed for internal luminaire temperatures of 30...40 °C; optimum luminous flux achieved at 35 °C	4050300464640
HE 35 W/830 ¹⁾	0.18 A A	LUMILUX Warm White	16 mm	116.45 g	1463.20 mm	Suitable for ECG operation only Lamp designed for internal luminaire temperatures of 30...40 °C; optimum luminous flux achieved at 35 °C	4050300464763
HE 35 W/840 ¹⁾	0.18 A A	LUMILUX Cool White	16 mm	116.45 g	1463.20 mm	Suitable for ECG operation only Lamp designed for internal luminaire temperatures of 30...40 °C; optimum luminous flux achieved at 35 °C	4050300464749

Karta katalogowa rodziny produktów

		Certyfikaty i Normy		Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)		
Opis produktu	Produkt zastępczy EAN	ZLDV_Energy efficiency class [AGGR]	ZLDV_Energy consumption [AGGR]	Date of Declaration	Primary Article Identifier	Declaration No. in SCIP database
HE 14 W/840 ¹⁾	4050300591384	F	14.00 kWh/1000h	18-04-2022	4050300464688 4050300591384	In work
HE 21 W/840 ¹⁾	4050300591407	F	21.00 kWh/1000h	18-04-2022	4050300591407 4050300464701	In work
HE 28 W/840 ¹⁾	4050300591421	F	29.00 kWh/1000h	18-04-2022	4050300591421 4050300464725	In work
HE 28 W/865 ¹⁾	4050300591346	F	29.00 kWh/1000h	18-04-2022	4050300591346	In work
HE 35 W/830 ¹⁾	4050300591469	F	35.00 kWh/1000h	18-04-2022	4050300591469 4050300464763	In work
HE 35 W/840 ¹⁾	4050300591445	F	35.00 kWh/1000h	18-04-2022	4050300591445 4050300464749	In work

¹⁾ Do zasilania tylko przez elektroniczny układ zasilający (EUZ)/Lampy przeznaczone do opraw o temperaturze wewnętrznej w zakresie 30...40 °C; optymalny strumień świetlny osiąga w temperaturze 35 °C

Karta katalogowa rodziny produktów



HE 14 W/840, HE 21 W/840, HE 28 W/840, HE 28 W/865, HE 35 W/830, HE 35 W/840

HE 14 W/840, HE 21 W/840, HE 28 W/840, HE 35 W/840

HE 28 W/865

HE 35 W/830

System Gwarancji

Gwarancja Systemowa OSRAM + w połączeniu z elektronicznymi układami zasilającymi OSRAM

Wskazówki dotyczące zastosowania

Więcej szczegółowych informacji dotyczących grafik i zastosowania znajduje się w karcie katalogowej produktu

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Dane logistyczne

Kod produktu	Opis produktu	Opakowanie (liczba produktów / opakowanie)	Wymiary (długość x szerokość x wysokość)	Objętość	Waga brutto
4050300464688	HE 14 W/840	Karton wysyłkowy 40	594 mm x 194 mm x 87 mm	10.03 dm ³	2668.00 g
4050300591384	HE 14 W/840	Karton wysyłkowy 20	587 mm x 110 mm x 90 mm	5.81 dm ³	1383.00 g
4050300591407	HE 21 W/840	Karton wysyłkowy 20	891 mm x 104 mm x 88 mm	8.15 dm ³	2283.00 g
4050300464725	HE 28 W/840	Karton wysyłkowy 40	1200 mm x 194 mm x 83 mm	19.32 dm ³	4813.00 g
4050300591421	HE 28 W/840	Karton wysyłkowy 20	1182 mm x 104 mm x 83 mm	10.20 dm ³	2713.00 g
4050300591346	HE 28 W/865	Karton wysyłkowy 20	1187 mm x 110 mm x 90 mm	11.75 dm ³	2934.00 g
4050300464763	HE 35 W/830	Karton wysyłkowy 40	1498 mm x 198 mm x 95 mm	28.18 dm ³	6587.00 g
4050300464749	HE 35 W/840	Karton wysyłkowy 40	1498 mm x 198 mm x 95 mm	28.18 dm ³	6587.00 g

Wymieniony kod produktu oznacza najmniejszą ilość produktu, jaka może być zamówiona. Jednostka transportowa może zawierać jedną sztukę lub więcej. Składając zamówienie prosimy o zamawianie ilości odpowiadających jednej lub wielokrotności jednostki transportowej.

Karta katalogowa rodziny produktów

Odnosińniki/lłącza

Więcej informacji na temat gwarancji systemowej oraz warunków gwarancji podano na stronie [https://](https://www.inventronics-light.com/multilevel-guarantees)

▶ www.inventronics-light.com/multilevel-guarantees

Oświadczenie

Zastrzega się możliwość zmian bez uprzedzenia. Błędy i ominięcia są możliwe. Należy zawsze upewnić się czy korzystasz z najnowszej wersji katalogu.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany