

Karta katalogowa rodziny produktów LUMILUX T8

Światłówki liniowe 26 mm, z trzonkiem G13



Dane techniczne							
Opis produktu	Dane elektryczne				Dane fotometryczne		
	ZLDV_Nominal current [AGGR]	ZLDV_Nominal voltage [AGGR]	ZLDV_Nominal wattage [AGGR]	ZLDV_Rated wattage [AGGR]	ZLDV_Light color (designation) [AGGR]	ZLDV_Color rendering index Ra [AGGR]	ZLDV_Rated luminous flux [AGGR]
L 15 W/827	0.31 A A				LUMILUX INTERNA		
L 15 W/830	0.31 A A				LUMILUX Warm White		
L 15 W/840	0.31 A A				LUMILUX Cool White		
L 15 W/865	0.31 A A				LUMILUX Cool Daylight		
L 16 W/830	0.2 A A				LUMILUX Warm White		
L 16 W/840	0.2 A A				LUMILUX Cool White		
L 18 W/840	0.37 A A				LUMILUX Cool White		
L 1800 W/840	0.37 A A	57 V	18,80 W	18,80 W	LUMILUX Cool White	≥80	1300 lm
L 23 W/840	0.29 A A				LUMILUX Cool White		
L 30 W/827	0.37 A A				LUMILUX INTERNA		
L 30 W/830	0.37 A A				LUMILUX Warm White		
L 30 W/840	0.37 A A				LUMILUX Cool White		
L 36 W/830	0.43 A A		36.00 W	36.00 W	LUMILUX Warm White	≥80	3350 lm
L 36 W/840	0.43 A A				LUMILUX Cool White		
L 36 W/880	0.43 A A				LUMILUX SKYWHITE		
L 38 W/840	0.43 A A				LUMILUX Cool White		
L 58 W/830	0.67 A A				LUMILUX Warm White		
L 58 W/840	0.67 A A				LUMILUX Cool White		

Karta katalogowa rodziny produktów

Opis produktu	Dane elektryczne				Dane fotometryczne		
	ZLDV_Nominal current [AGGR]	ZLDV_Nominal voltage [AGGR]	ZLDV_Nominal wattage [AGGR]	ZLDV_Rated wattage [AGGR]	ZLDV_Light color (designation) [AGGR]	ZLDV_Color rendering index Ra [AGGR]	ZLDV_Rated luminous flux [AGGR]
L 58 W/865	0.67 A A				LUMILUX Cool Daylight		
L 58 W/880	0.67 A A				LUMILUX SKYWHITE		

Opis produktu	ZLDV_Light color [AGGR]	ZLDV_Rated color temperature [AGGR]	ZLDV_Nominal luminous flux [AGGR]	ZLDV_Color temperature [AGGR]	Wymiary i waga		
					ZLDV_Tube diameter [AGGR]	ZLDV_Product weight [AGGR]	ZLDV_Overall length [AGGR]
L 15 W/827					26 mm	60.00 g	451.60 mm
L 15 W/830					26 mm	60.00 g	451.60 mm
L 15 W/840					26 mm	60.00 g	451.60 mm
L 15 W/865					26 mm	60.00 g	451.60 mm
L 16 W/830					26 mm	100.00 g	734.20 mm
L 16 W/840					26 mm	100.00 g	734.20 mm
L 18 W/840					26 mm	77.00 g	604.00 mm
L 1800 W/840	840	4000 K	1300 lm	4000 K	26 mm	77.00 g	604.00 mm
L 23 W/840					26 mm	130.00 g	984.20 mm
L 30 W/827					26 mm	120.00 g	908.80 mm
L 30 W/830					26 mm	120.00 g	908.80 mm
L 30 W/840					26 mm	120.00 g	908.80 mm
L 36 W/830	830	3000 K	3350 lm	3000 K	26 mm	149.00 g	1213.60 mm
L 36 W/840					26 mm	160.00 g	1213.60 mm
L 36 W/880					26 mm	160.00 g	1213.60 mm
L 38 W/840					26 mm	130.00 g	1061.20 mm
L 58 W/830					26 mm	190.00 g	1514.20 mm
L 58 W/840					26 mm	190.00 g	1514.20 mm
L 58 W/865					26 mm	190.00 g	1514.20 mm

Karta katalogowa rodziny produktów

					Wymiary i waga		
Opis produktu	ZLDV_Light color [AGGR]	ZLDV_Rated color temperature [AGGR]	ZLDV_Nominal luminous flux [AGGR]	ZLDV_Color temperature [AGGR]	ZLDV_Tube diameter [AGGR]	ZLDV_Product weight [AGGR]	ZLDV_Overall length [AGGR]
L 58 W/880					26 mm	190.00 g	1514.20 mm
				Certyfikaty i Normy		Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Opis produktu	ZLDV_Length [AGGR]	ZLDV_Diameter [AGGR]	ZLDV_Outer bulb [AGGR]	ZLDV_Energy efficiency class [AGGR]	ZLDV_Energy consumption [AGGR]	Date of Declaration	Primary Article Identifier
L 15 W/827				G	15.00 kWh/1000h	19-01-2022	4050300446042
L 15 W/830				G	15.00 kWh/1000h	19-01-2022	4050300446028
L 15 W/840				G	15.00 kWh/1000h	19-01-2022	4050300446004
L 15 W/865				G	15.00 kWh/1000h	19-01-2022	4050300446189
L 16 W/830				G	17.00 kWh/1000h	19-01-2022	4008321959065
L 16 W/840				G	17.00 kWh/1000h	19-01-2022	4050300446066
L 18 W/840				G	19.00 kWh/1000h	30-06-2022	4050300517797
L 1800 W/840	604,0 mm	25,5 mm	T26	G	19.00 kWh/1000h	19-01-2022	4050300443409
L 23 W/840				G	24.00 kWh/1000h	19-01-2022	4050300446240
L 30 W/827				G	32.00 kWh/1000h	19-01-2022	4050300518077
L 30 W/830				G	32.00 kWh/1000h	19-01-2022	4050300518053
L 30 W/840				G	32.00 kWh/1000h	19-01-2022	4050300518039
L 36 W/830	1200 mm	26.0 mm	T26	G	43 kWh/1000h	19-01-2022	4050300443324 4050300517896
L 36 W/840				G	40.00 kWh/1000h	19-01-2022	4050300517872 4050300518091
L 36 W/880				G	39.00 kWh/1000h	19-01-2022	4008321002976
L 38 W/840				G	40.00 kWh/1000h	19-01-2022	4050300518138
L 58 W/830				G	62.00 kWh/1000h	19-01-2022	4050300517971
L 58 W/840				G	62.00 kWh/1000h	30-06-2022	4050300517957


Karta katalogowa rodziny produktów

				Certyfikaty i Normy		Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Opis produktu	ZLDV_Length [AGGR]	ZLDV_Diameter [AGGR]	ZLDV_Outer bulb [AGGR]	ZLDV_Energy efficiency class [AGGR]	ZLDV_Energy consumption [AGGR]	Date of Declaration	Primary Article Identifier
L 58 W/865				G	62.00 kWh/1000h	19-01-2022	4050300517933
L 58 W/880				G	62.00 kWh/1000h	19-01-2022	4008321002990

		Dodatkowe dane produktu		
Opis produktu	Declaration No. in SCIP database	Produkt zastępczy EAN	ZLDV_Base (standard designation) [AGGR]	Produkt zastępczy EAN
L 15 W/827	In work			
L 15 W/830	In work			
L 15 W/840	In work			
L 15 W/865	In work			
L 16 W/830	In work			
L 16 W/840	In work			
L 18 W/840	In work	4050300443409		
L 1800 W/840	In work		G13	4050300517797
L 23 W/840	In work			
L 30 W/827	In work			
L 30 W/830	In work			
L 30 W/840	In work			
L 36 W/830	In work	4050300443324	G13	4050300517896
L 36 W/840	In work	4050300443300		4050300517872
L 36 W/880	In work			
L 38 W/840	In work			
L 58 W/830	In work	4050300470382		4050300517971
L 58 W/840	In work	4050300443362		

Karta katalogowa rodziny produktów

Opis produktu	Declaration No. in SCIP database	Dodatkowe dane produktu		
		Produkt zastępczy EAN	ZLDV_Base (standard designation) [AGGR]	Produkt zastępczy EAN
L 58 W/865	In work			
L 58 W/880	In work			



L 15 W/827, L 15 W/830, L 15 W/840, L 15 W/865, L 16 W/830, L 16 W/840, L 18 W/840, L 1800 W/840, L 23 W/840, L 30 W/827, L 30 W/830, L 30 W/840, L 36 W/830, L 36 W/840, L 36 W/880, L 38 W/840, L 58 W/830, L 58 W/840, L 58 W/865, L 58 W/880

L 15 W/827, L 30 W/827

L 15 W/830, L 16 W/830, L 30 W/830, L 36 W/830, L 58 W/830

L 15 W/840, L 16 W/840, L 18 W/840, L 23 W/840, L 30 W/840, L 36 W/840, L 38 W/840, L 58 W/840

L 15 W/865, L 58 W/865

L 36 W/880, L 58 W/880

System Gwarancji

Gwarancja Systemowa OSRAM + w połączeniu z elektronicznymi układami zasilającymi OSRAM

Wskazówki dotyczące zastosowania

Więcej szczegółowych informacji dotyczących grafik i zastosowania znajduje się w karcie katalogowej produktu

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Dane logistyczne

Kod produktu	Opis produktu	Opakowanie (liczba produktów / opakowanie)	Wymiary (długość x szerokość x wysokość)	Objętość	Waga brutto
4050300446042	L 15 W/827	Karton wysyłkowy 25	508 mm x 155 mm x 147 mm	11.57 dm ³	2594.00 g
4050300446028	L 15 W/830	Karton wysyłkowy 25	142 mm x 145 mm x 480 mm	9.88 dm ³	2009.00 g
4050300446004	L 15 W/840	Karton wysyłkowy 25	142 mm x 145 mm x 480 mm	9.88 dm ³	2009.00 g
4050300446189	L 15 W/865	Karton wysyłkowy 25	142 mm x 145 mm x 480 mm	9.88 dm ³	2034.00 g
4008321959065	L 16 W/830	Karton wysyłkowy 25	142 mm x 145 mm x 762 mm	15.69 dm ³	3161.00 g
4050300446066	L 16 W/840	Karton wysyłkowy 25	142 mm x 145 mm x 762 mm	15.69 dm ³	3152.00 g
4050300517797	L 18 W/840	Karton wysyłkowy 25	142 mm x 145 mm x 632 mm	13.01 dm ³	2595.00 g
4050300443409	L 1800 W/840	Karton wysyłkowy 30	659 mm x 226 mm x 206 mm	30.68 dm ³	2941.00 g
4050300446240	L 23 W/840	Karton wysyłkowy 25	142 mm x 145 mm x 1032 mm	21.25 dm ³	4142.00 g

Dane logistyczne

4050300518077	L 30 W/827	Karton wysyłkowy 25	142 mm x 145 mm x 937 mm	19.29 dm ³	3910.00 g
4050300518053	L 30 W/830	Karton wysyłkowy 25	781 mm x 304 mm x 145 mm	34.43 dm ³	3910.00 g
4050300518039	L 30 W/840	Karton wysyłkowy 25	142 mm x 145 mm x 937 mm	19.29 dm ³	3910.00 g
4050300517896	L 36 W/830	Karton wysyłkowy 25	144 mm x 147 mm x 1242 mm	26.29 dm ³	5535.00 g
4050300517872	L 36 W/840	Karton wysyłkowy 25	142 mm x 145 mm x 1242 mm	25.57 dm ³	5062.00 g
4050300518091	L 36 W/840	Karton wysyłkowy 25	142 mm x 145 mm x 1032 mm	21.25 dm ³	4216.00 g
4008321002976	L 36 W/880	Karton wysyłkowy 25	142 mm x 145 mm x 1242 mm	25.57 dm ³	5062.00 g
4050300518138	L 38 W/840	Karton wysyłkowy 25	142 mm x 145 mm x 1089 mm	22.42 dm ³	4535.00 g
4050300517971	L 58 W/830	Karton wysyłkowy 25	142 mm x 145 mm x 1542 mm	31.75 dm ³	6320.00 g
4050300517957	L 58 W/840	Karton wysyłkowy 25	142 mm x 145 mm x 1542 mm	31.75 dm ³	6320.00 g
4050300517933	L 58 W/865	Karton wysyłkowy 25	142 mm x 145 mm x 1542 mm	31.75 dm ³	6320.00 g
4008321002990	L 58 W/880	Karton wysyłkowy 25	142 mm x 145 mm x 1542 mm	31.75 dm ³	6314.00 g

Wymieniony kod produktu oznacza najmniejszą ilość produktu, jaka może być zamówiona. Jednostka transportowa może zawierać jedną sztukę lub więcej. Składając zamówienie prosimy o zamawianie ilości odpowiadających jednej lub wielokrotności jednostki transportowej.

Odnosiniki/łącza

Więcej informacji na temat gwarancji systemowej oraz warunków gwarancji podano na stronie [https://](https://www.inventronics-light.com/multilevel-guarantees)

▶ www.inventronics-light.com/multilevel-guarantees

Więcej informacji na temat elektronicznych układów zasilających QUICKTRONIC na stronie

▶ www.osram.com/QUICKTRONIC

Oświadczenie

Zastrzega się możliwość zmian bez uprzedzenia. Błędy i ominięcia są możliwe. Należy zawsze upewnić się czy korzystasz z najnowszej wersji katalogu.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany