

Karta katalogowa produktu

L 1800 W/840

LUMILUX T8 | Światłówki liniowe 26 mm, z trzonkiem G13



Dane techniczne


Dane elektryczne

ZLDV_Nominal voltage [AGGR]	57 V
ZLDV_Nominal wattage [AGGR]	18,80 W
ZLDV_Rated lamp efficacy (HF data 25 °C) [AGGR]	Under clarification by authority and standardization body
ZLDV_Rated wattage [AGGR]	18,80 W
ZLDV_Lamp current [AGGR]	0,37 A
ZLDV_Nominal current [AGGR]	0.37 A A

Dane fotometryczne

ZLDV_Rated lamp efficacy (standard condition) [AGGR]	75 lm/W
ZLDV_Color rendering index Ra [AGGR]	≥80
ZLDV_Rated luminous flux [AGGR]	1300 lm
ZLDV_Luminous flux at 25 °C [AGGR]	1350 lm
ZLDV_Light color [AGGR]	840
ZLDV_Rated color temperature [AGGR]	4000 K
ZLDV_Nominal luminous flux [AGGR]	1300 lm
ZLDV_Light color (designation) [AGGR]	LUMILUX Cool White
ZLDV_Rated LLMF at 2,000 h [AGGR]	0.96
ZLDV_Rated LLMF at 4,000 h [AGGR]	0.94
ZLDV_Rated LLMF at 6,000 h [AGGR]	0.93
ZLDV_Rated LLMF at 8,000 h [AGGR]	0.91
ZLDV_Rated LLMF at 12,000 h [AGGR]	0.91
ZLDV_Rated LLMF at 16,000 h [AGGR]	0.9
ZLDV_Rated LLMF at 20,000 h [AGGR]	0.96
ZLDV_Color temperature [AGGR]	4000 K
ZLDV_Luminous flux [AGGR]	1300 lm

Wymiary i waga



ZLDV_Tube diameter [AGGR]	26 mm
ZLDV_Length [AGGR]	604,0 mm
ZLDV_Length with base excl. base pins/connection [AGGR]	590,00 mm
ZLDV_Diameter [AGGR]	25,5 mm
ZLDV_Product weight [AGGR]	77.00 g
ZLDV_Outer bulb [AGGR]	T26
ZLDV_Overall length [AGGR]	604.00 mm
ZLDV_Maximum diameter [AGGR]	26,0 mm

Temperatury i warunki pracy

ZLDV_Rated ambient temp.w.max.luminous flux [AGGR]	25,0 °C
--	---------

Trwałość

ZLDV_Service life [AGGR]	18000 h ¹⁾
ZLDV_Lifespan [AGGR]	20000 h ¹⁾
ZLDV_Rated lamp survival factor at 2,000 h [AGGR]	0,99
ZLDV_Rated lamp survival factor at 4,000 h [AGGR]	0,99
ZLDV_Rated lamp survival factor at 6,000 h [AGGR]	0,99
ZLDV_Rated lamp survival factor at 8,000 h [AGGR]	0,99
ZLDV_Rated lamp survival factor at 12,000 h [AGGR]	0,99
ZLDV_Rated lamp survival factor at 16,000 h [AGGR]	0,99
ZLDV_Rated lamp survival factor at 20,000 h [AGGR]	0,50
ZLDV_Operation mode LLMF/LSF [AGGR]	HF
ZLDV_Rated lamp life time [AGGR]	20000 h

¹⁾ Con preriscaldamento ECG

Karta katalogowa produktu

Dodatkowe dane produktu

ZLDV_Base (standard designation) [AGGR]	G13
ZLDV_Mercury content [AGGR]	3.0 mg
Zgodnie z Dyrektywą WEEE	Tak
Produkt zastępczy EAN	4050300517797

Możliwości

ZLDV_Dimmable [AGGR]	Si
ZLDV_Suitable for indoor [AGGR]	Ja

Certyfikaty i Normy

ZLDV_Energy efficiency class [AGGR]	G
ZLDV_Energy consumption [AGGR]	19.00 kWh/1000h

Kraj - specyficzna kategoryzacja

ZLDV_Order reference [AGGR]	L 18W/840
-----------------------------	-----------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	19-01-2022
Primary Article Identifier	4050300443409
Declaration No. in SCIP database	In work

System Gwarancji

Gwarancja Systemowa OSRAM + w połączeniu z elektronicznymi układami zasilającymi OSRAM

DUO CIRCUIT

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Dane logistyczne

Kod produktu	Opis produktu	Opakowanie (liczba produktów / opakowanie)	Wymiary (długość x szerokość x wysokość)	Objętość	Waga brutto
4050300443409	L 1800 W/840	Karton wysylkowy 30 Pieces Nieopakowane	659 mm x 226 mm x 206 mm	30.68 dm ³	2941.00 g

Wymieniony kod produktu oznacza najmniejszą ilość produktu, jaka może być zamówiona. Jednostka transportowa może zawierać jedną sztukę lub więcej. Składając zamówienie prosimy o zamawianie ilości odpowiadających jednej lub wielokrotności jednostki transportowej.

Odnosiniki/łącza

Więcej informacji na temat gwarancji systemowej oraz warunków gwarancji podano na stronie [https://](https://www.inventronics-light.com/multilevel-guarantees)

▶ www.inventronics-light.com/multilevel-guarantees

Więcej informacji na temat elektronicznych układów zasilających QUICKTRONIC na stronie

▶ www.osram.com/QUICKTRONIC

Oświadczenie

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany