LINEARlight FLEX Tunable White IP00

Liniowe moduły LED przeznaczone do uniwersalnych i zindywidualizowanych rozwiązań oświetleniowych



Cechy produktu

- 24 V LED strips flexible and cuttable
- Up to 60,000 h L90/B10 with SDT technology, tested acc. to IEC 62717 on real LED strips
- Adjustable color temp. via Tunable White: 2200...3500 K, 2500...4000 K, 2700...5700 K CRI90
- Adjustable color temp. via Tunable White: 2200...3500 K, 2500...3500 K, 2700...6500 K CRI80
- CRI80, CRI90 options available
- Stable light flux over length: active constant current regulators (ICs), PWM safe
- Embedded automatic quick protection against accidental miswiring up to 25 V
- Fully PWM dimmable from zero up to 2.5 kHz, audible noise free, suitable for quite places
- Designed, engineered and manufactured and tested in Italy (ISO9001, ISO 17025, ACCREDIA, VDE)

Korzyści ze stosowania produktu

- Color uniformity better than 3 SDCM on the entire LED strip and between strips
- LED lifetime acc.to IES LM-80 and IES TM-21 standards, and also internal OSRAM LAB tests
- Excellent robustness: single reel manufacturing technology (no solder joints on strip)
- Łatwy montaż na wielu delikatnych powierzchniach dzięki taśmie samoprzylepnej z tyłu
- Wyjątkowe wzornictwo i wysoka jakość materiałów
- Pre-soldered wires

Obszar zastosowań

- Oświetlenie faset
- Oświetlenie sklepowe
- Biura

© 2024, Inventronics GmbH. Wszelkie prawa zastrzeżone. Inventronics jest licencjobiorcą marki OSRAM. OSRAM jest znakiem towarowym firmy ams OSRAM.

Dane techniczne

	Dane elektryczne						Dane fotometryczne
Opis produktu	**Napięcie nominalne**	**Rodzaj prądu**	**Nominalna moc na metr**	**Moc znamionowa**	**Zakres napięcia wejściowego**	**Accidental reverse input voltage protection up to**	**Barwa światła LED**
LF3400TW-G5 -927.965-03 L1	24,0 V	DC	30.9 W	92,70 W	23…25 V	25 V	Dynamic White
LF3400TW-G5 -927.957-03 L1	24,0 V	DC	30.2 W	90,70 W	23…25 V	25 V	Dynamic White
LF3400TW-G5 -925.940-03 L1	24,0 V	DC	32.4 W	97,30 W	23…25 V	25 V	Dynamic White
LF3400TW-G5 -922.935-03 L1	24,0 V	DC	34.7 W	104,00 W	23…25 V	25 V	Dynamic White
LF1100TW-G5 -927.965-09 L2	24,0 V	DC	9,8 W	88,40 W	23…25 V	25 V	Dynamic White
LF1100TW-G5 -927.957-09 L2	24,0 V	DC	9,8 W	88,40 W	23…25 V	25 V	Dynamic White
LF1100TW-G5 -925.940-09 L2	24,0 V	DC	10,4 W	93,60 W	23…25 V	25 V	Dynamic White
LF1100TW-G5 -922.935-09 L2	24,0 V	DC	10,9 W	98,50 W	23…25 V	25 V	Dynamic White

						Wymiary i waga
Opis produktu	**Ogólny wskaźnik oddawania barw Ra**	**Strumień świetlny na metr**	**Skuteczność świetlna**	**Standardowe odchylenie dopasowania barw**	**Barwa światła (oznaczenie)**	**Długość**
LF3400TW-G5 -927.965-03 L1	90	3400 lm	110 lm/W	≤3 sdcm	2700…6500 K	3000,0 mm
LF3400TW-G5 -927.957-03 L1	90	3400 lm	113 lm/W	≤3 sdcm	2700…5700 K	3000,0 mm
LF3400TW-G5 -925.940-03 L1	90	3400 lm	105 lm/W	≤3 sdcm	2500…4000 K	3000,0 mm
LF3400TW-G5 -922.935-03 L1	90	3400 lm	98 lm/W	≤3 sdcm		3000,0 mm
LF1100TW-G5 -927.965-09 L2	90	1156 lm	118 lm/W	≤3 sdcm	2700…6500 K	9000,0 mm
LF1100TW-G5 -927.957-09 L2	90	1156 lm	118 lm/W	≤3 sdcm	2700…5700 K	9000,0 mm
LF1100TW-G5 -925.940-09 L2	90	1156 lm	111 lm/W	≤3 sdcm	2500…4000 K	9000,0 mm
LF1100TW-G5 -922.935-09 L2	90	1111 lm	102 lm/W	≤3 sdcm		9000,0 mm

			Temperatury i warunki pracy		Dodatkowe dane produktu
Opis produktu	**Długość przewodów**	**Masa produktu**	**Zakres temperatury pracy**	**Zakres temperatury magazynowania**	**ID of contained light source [AGGR]**
LF3400TW-G5 -927.965-03 L1	500,0	35,00 g	-20…+85 °C [1)]	-40…+85 °C	LS_TRV_286287
LF3400TW-G5 -927.957-03 L1	500,0	35,00 g	-20…+85 °C [1)]	-40…85 °C	LS_TRV_286066

© 2024, Inventronics GmbH. Wszelkie prawa zastrzeżone. Inventronics jest licencjobiorcą marki OSRAM. OSRAM jest znakiem towarowym firmy ams OSRAM.

Karta katalogowa rodziny produktów

			Temperatury i warunki pracy		Dodatkowe dane produktu
Opis produktu	**Długość przewodów**	**Masa produktu**	**Zakres temperatury pracy**	**Zakres temperatury magazynowania**	**ID of contained light source [AGGR]**
LF3400TW-G5 -925.940-03 L1	500,0	35,00 g	-20…+85 °C [1)]	-40…85 °C	LS_TRV_286065
LF3400TW-G5 -922.935-03 L1	500,0	35,00 g	-20…+85 °C [1)]	-40…85 °C	LS_TRV_286064
LF1100TW-G5 -927.965-09 L2	500,0	104,00 g	-20…+85 °C [1)]	-40…+85 °C	LS_TRV_286286
LF1100TW-G5 -927.957-09 L2	500,0	104,00 g	-20…+85 °C [1)]	-40…85 °C	LS_TRV_286063
LF1100TW-G5 -925.940-09 L2	500,0	104,00 g	-20…+85 °C [1)]	-40…85 °C	LS_TRV_286062
LF1100TW-G5 -922.935-09 L2	500,0	104,00 g	-20…+85 °C [1)]	-40…85 °C	LS_TRV_286061

		Możliwości	Certyfikaty i Normy	
Opis produktu	**Produkt zastępczy EAN**	**Ściemnianie**	**Energy efficiency class of the contained light source**	**Normy**
LF3400TW-G5 -927.965-03 L1		Tak	F	
LF3400TW-G5 -927.957-03 L1	4062172032605, 4062172032629		F	CE/ENEC/EAC
LF3400TW-G5 -925.940-03 L1			F	CE/ENEC/EAC
LF3400TW-G5 -922.935-03 L1	4052899563339		F	CE/ENEC/EAC
LF1100TW-G5 -927.965-09 L2		Tak	F	
LF1100TW-G5 -927.957-09 L2	4062172032667, 4062172032643		F	CE/ENEC/EAC
LF1100TW-G5 -925.940-09 L2			F	CE/ENEC/EAC
LF1100TW-G5 -922.935-09 L2			F	CE/ENEC/EAC

	Dane logistyczne	Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Opis produktu	**Kod taryfy celnej**	**Date of Declaration**	**Primary Article Identifier**	**Candidate List Substance 1**
LF3400TW-G5 -927.965-03 L1	85395100000	26-05-2023	4062172263719	Lead
LF3400TW-G5 -927.957-03 L1	85395100000	09-06-2023	4062172189354	Lead
LF3400TW-G5 -925.940-03 L1	85395100000	09-06-2023	4062172189330	Lead
LF3400TW-G5 -922.935-03 L1	85395100000	09-06-2023	4062172189316	Lead
LF1100TW-G5 -927.965-09 L2	85395100000	19-05-2023	4062172263696	Lead
LF1100TW-G5 -927.957-09 L2	85395100000	09-06-2023	4062172189293	Lead
LF1100TW-G5 -925.940-09 L2	85395100000	09-06-2023	4062172189279	Lead
LF1100TW-G5 -922.935-09 L2	85395100000	09-06-2023	4062172189255	Lead

Opis produktu	**CAS No. of substance 1**	**Safe Use Instruction**	**Declaration No. in SCIP database**
LF3400TW-G5 -927.965-03 L1	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	3d44363c-fe56-4bbd-97a6-860743cbd9c5


© 2024, Inventronics GmbH. Wszelkie prawa zastrzeżone. Inventronics jest licencjobiorcą marki OSRAM. OSRAM jest znakiem towarowym firmy ams OSRAM.

Opis produktu	CAS No. of substance 1	Safe Use Instruction	Declaration No. in SCIP database
LF3400TW-G5 -927.957-03 L1	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	6dfc036b-ceb0-4e6b-9095-48384a422e91
LF3400TW-G5 -925.940-03 L1	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	3b0dc5f1-547b-441b-bd5e-9960b615b212
LF3400TW-G5 -922.935-03 L1	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	9c2d531d-dbbb-487a-b4d4-50328cc7dc74
LF1100TW-G5 -927.965-09 L2	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	d751d4ed-f883-4c1c-834c-4e9ef2896222
LF1100TW-G5 -927.957-09 L2	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	1e4aef2d-5fd2-4940-9779-142c985ead14
LF1100TW-G5 -925.940-09 L2	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	39d314f8-b6f9-41f5-acad-622e0887ed2a
LF1100TW-G5 -922.935-09 L2	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	103ac832-f72b-4c34-b09f-89e3b075d569


[1] Exceeding the maximum ratings will reduce expected life time or destroy the LED strip.

© 2024, Inventronics GmbH. Wszelkie prawa zastrzeżone. Inventronics jest licencjobiorcą marki OSRAM. OSRAM jest znakiem towarowym firmy ams OSRAM.

Karta katalogowa rodziny produktów



LINEARlight Flex Tunable White IP00 L1 drawing



LINEARlight Flex Tunable White IP00 L2

Wyposażenie / Akcesoria

- Uproszczone połączenie z dopasowanym systemem CONNECTsystem jako opcja
- Perfectly matched with OTi DALI 50/80 4CH DT6/8 and OTi DALI 160 2CH DT6/8
- Perfectly matched with OTi BLE 80/220-240/24 4CH

Wskazówki dotyczące zastosowania

Więcej szczegółowych informacji dotyczących grafik i zastosowania znajduje się w karcie katalogowej produktu

Karta katalogowa, teks

- not relevant
- not relevant
- not relevant
- Avoid installations in rural and urban areas with high industrial activity and heavy traffic (higher than class than 4C1 according IEC 60721-3) and as well as installation in spa, areas with chlorine atmosphere, direct exposure to blown sand.

Sprzedaż i pomoc techniczna

Sprzedaż i pomoc techniczna www.osram.com

Pobierz dane

	Plik
	User instruction LINEARlight FLEX, Tunable White
	Product Datasheet LINEARlight Flex Tunable White CRI90 Specification Sheet (EN)

© 2024, Inventronics GmbH. Wszelkie prawa zastrzeżone. Inventronics jest licencjobiorcą marki OSRAM. OSRAM jest znakiem towarowym firmy ams OSRAM.

Karta katalogowa rodziny produktów

	Broszury Light is freedom of design (EN)
	Certyfikaty VDE ENEC CERTIFICATE 40052516 160823
	Certyfikaty LF(P) TW G5 CB 180121
	Deklaracje zgodności LR FLEX TW2 CE 4249165 02 020823
	Eulumdat LF3400TW-G5-927.957-03 L1 LTD 130421
	IES data LF3400TW-G5-927.957-03 L1 IES 130421
	Eulumdat LF3400TW-G5-925.940-03 L1 LTD 130421
	IES data LF3400TW-G5-925.940-03 L1 IES 130421
	Eulumdat LF3400TW-G5-922.935-03 L1 LTD 130421
	IES data LF3400TW-G5-922.935-03 L1 IES 130421
	Eulumdat LF1100TW-G5-927.957-09 L2 LTD 130421
	IES data LF1100TW-G5-927.957-09 L2 IES 130421
	Eulumdat LF1100TW-G5-925.940-09 L2 LTD 130421
	IES data LF1100TW-G5-925.940-09 L2 IES 130421
	Eulumdat LF1100TW-G5-922.935-09 L2 LTD 130421
	IES data LF1100TW-G5-922.935-09 L2 IES 130421

© 2024, Inventronics GmbH. Wszelkie prawa zastrzeżone. Inventronics jest licencjobiorcą marki OSRAM. OSRAM jest znakiem towarowym firmy ams OSRAM.

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer.In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer.Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Dane logistyczne

Kod produktu	Opis produktu	Opakowanie (liczba produktów / opakowanie)	Wymiary (długość x szerokość x wysokość)	Objętość	Waga brutto
4062172263719	LF3400TW-G5 -927.965-03 L1	Karton wysyłkowy 8	241 mm x 195 mm x 205 mm	9.63 dm^3	1213.00 g
4062172189354	LF3400TW-G5 -927.957-03 L1	Karton wysyłkowy 8	241 mm x 195 mm x 205 mm	9.63 dm^3	1213.00 g
4062172189330	LF3400TW-G5 -925.940-03 L1	Karton wysyłkowy 8	241 mm x 195 mm x 205 mm	9.63 dm^3	1213.00 g
4062172189316	LF3400TW-G5 -922.935-03 L1	Karton wysyłkowy 8	241 mm x 195 mm x 205 mm	9.63 dm^3	1213.00 g
4062172263696	LF1100TW-G5 -927.965-09 L2	Karton wysyłkowy 8	241 mm x 195 mm x 205 mm	9.63 dm^3	1765.00 g
4062172189293	LF1100TW-G5 -927.957-09 L2	Karton wysyłkowy 8	241 mm x 195 mm x 205 mm	9.63 dm^3	1765.00 g
4062172189279	LF1100TW-G5 -925.940-09 L2	Karton wysyłkowy 8	241 mm x 195 mm x 205 mm	9.63 dm^3	1765.00 g
4062172189255	LF1100TW-G5 -922.935-09 L2	Karton wysyłkowy 8	241 mm x 195 mm x 205 mm	9.63 dm^3	1765.00 g

Wymieniony kod produktu oznacza najmniejszą ilość produktu, jaka może być zamówiona. Jednostka transportowa może zawierać jedną sztukę lub więcej. Składając zamówienie prosimy o zamawianie ilości odpowiadających jednej lub wielokrotności jednostki transportowej.

Akcesoria opcjonalne

© 2024, Inventronics GmbH. Wszelkie prawa zastrzeżone. Inventronics jest licencjobiorcą marki OSRAM. OSRAM jest znakiem towarowym firmy ams OSRAM.

Karta katalogowa rodziny produktów

Opis produktu	Nazwa akcesorium	Kod akcesorium
LF3400TW-G5 -927.965-03 L1	CORNER-FLEX -4P-003 KIT 10PCS	4062172179638
LF3400TW-G5 -927.965-03 L1	CORNER-FLEX -4P-015 KIT 10PCS	4062172179676
LF3400TW-G5 -927.965-03 L1	CONN-FLEX -3P-050 KIT 10PCS	4062172179690
LF3400TW-G5 -927.965-03 L1	CONN-FLEX -3P-200 KIT 10PCS	4062172179720
LF3400TW-G5 -927.965-03 L1	LTS-SLIMTRACK -2000 KIT 5 PCS	4062172207300
LF3400TW-G5 -927.965-03 L1	FX-QMS-G1 -TU15H6-300	4052899448865
LF3400TW-G5 -927.965-03 L1	FX-QMS-G1 -TU15H6W3-300	4052899448889
LF3400TW-G5 -927.965-03 L1	FX-QMS-G1 -TU16H12W3-300	4052899448988
LF3400TW-G5 -927.965-03 L1	FX-QMS-G1 -TU16H12-300	4052899448964
LF3400TW-G5 -927.965-03 L1	FX -SC08-G2-CT4PJ	4052899464858
LF3400TW-G5 -927.965-03 L1	FX-QMS-G1 -TU16H12LS-300	4052899449046
LF3400TW-G5 -927.957-03 L1	CORNER-FLEX -4P-003 KIT 10PCS	4062172179638
LF3400TW-G5 -927.957-03 L1	CORNER-FLEX -4P-015 KIT 10PCS	4062172179676
LF3400TW-G5 -927.957-03 L1	CONN-FLEX -3P-050 KIT 10PCS	4062172179690
LF3400TW-G5 -927.957-03 L1	CONN-FLEX -3P-200 KIT 10PCS	4062172179720
LF3400TW-G5 -927.957-03 L1	LTS-SLIMTRACK -2000 KIT 5 PCS	4062172207300
LF3400TW-G5 -927.957-03 L1	FX-QMS-G1 -TU15H6-300	4052899448865
LF3400TW-G5 -927.957-03 L1	FX-QMS-G1 -TU15H6W3-300	4052899448889
LF3400TW-G5 -927.957-03 L1	FX-QMS-G1 -TU16H12W3-300	4052899448988
LF3400TW-G5 -927.957-03 L1	FX-QMS-G1 -TU16H12-300	4052899448964
LF3400TW-G5 -927.957-03 L1	FX -SC08-G2-CT4PJ	4052899464858
LF3400TW-G5 -927.957-03 L1	FX-QMS-G1 -TU16H12LS-300	4052899449046
LF3400TW-G5 -925.940-03 L1	CORNER-FLEX -4P-003 KIT 10PCS	4062172179638
LF3400TW-G5 -925.940-03 L1	CORNER-FLEX -4P-015 KIT 10PCS	4062172179676
LF3400TW-G5 -925.940-03 L1	CONN-FLEX -3P-050 KIT 10PCS	4062172179690
LF3400TW-G5 -925.940-03 L1	CONN-FLEX -3P-200 KIT 10PCS	4062172179720
LF3400TW-G5 -925.940-03 L1	LTS-SLIMTRACK -2000 KIT 5 PCS	4062172207300
LF3400TW-G5 -925.940-03 L1	FX-QMS-G1 -TU15H6-300	4052899448865
LF3400TW-G5 -925.940-03 L1	FX-QMS-G1 -TU15H6W3-300	4052899448889
LF3400TW-G5 -925.940-03 L1	FX-QMS-G1 -TU16H12W3-300	4052899448988
LF3400TW-G5 -925.940-03 L1	FX-QMS-G1 -TU16H12-300	4052899448964
LF3400TW-G5 -925.940-03 L1	FX -SC08-G2-CT4PJ	4052899464858
LF3400TW-G5 -925.940-03 L1	FX-QMS-G1 -TU16H12LS-300	4052899449046
LF3400TW-G5 -922.935-03 L1	CORNER-FLEX -4P-003 KIT 10PCS	4062172179638
LF3400TW-G5 -922.935-03 L1	CORNER-FLEX -4P-015 KIT 10PCS	4062172179676
LF3400TW-G5 -922.935-03 L1	CONN-FLEX -3P-050 KIT 10PCS	4062172179690
LF3400TW-G5 -922.935-03 L1	CONN-FLEX -3P-200 KIT 10PCS	4062172179720

© 2024, Inventronics GmbH. Wszelkie prawa zastrzeżone. Inventronics jest licencjobiorcą marki OSRAM. OSRAM jest znakiem towarowym firmy ams OSRAM.

LF3400TW-G5 -922.935-03 L1	LTS-SLIMTRACK -2000 KIT 5 PCS	4062172207300
LF3400TW-G5 -922.935-03 L1	FX-QMS-G1 -TU15H6-300	4052899448865
LF3400TW-G5 -922.935-03 L1	FX-QMS-G1 -TU15H6W3-300	4052899448889
LF3400TW-G5 -922.935-03 L1	FX-QMS-G1 -TU16H12W3-300	4052899448988
LF3400TW-G5 -922.935-03 L1	FX-QMS-G1 -TU16H12-300	4052899448964
LF3400TW-G5 -922.935-03 L1	FX -SC08-G2-CT4PJ	4052899464858
LF3400TW-G5 -922.935-03 L1	FX-QMS-G1 -TU16H12LS-300	4052899449046
LF1100TW-G5 -927.965-09 L2	CORNER-FLEX -4P-003 KIT 10PCS	4062172179638
LF1100TW-G5 -927.965-09 L2	CORNER-FLEX -4P-015 KIT 10PCS	4062172179676
LF1100TW-G5 -927.965-09 L2	CONN-FLEX -3P-050 KIT 10PCS	4062172179690
LF1100TW-G5 -927.965-09 L2	CONN-FLEX -3P-200 KIT 10PCS	4062172179720
LF1100TW-G5 -927.965-09 L2	LTS-SLIMTRACK -2000 KIT 5 PCS	4062172207300
LF1100TW-G5 -927.965-09 L2	FX-QMS-G1 -TU15H6-300	4052899448865
LF1100TW-G5 -927.965-09 L2	FX-QMS-G1 -TU15H6W3-300	4052899448889
LF1100TW-G5 -927.965-09 L2	FX-QMS-G1 -TU16H12W3-300	4052899448988
LF1100TW-G5 -927.965-09 L2	FX-QMS-G1 -TU16H12-300	4052899448964
LF1100TW-G5 -927.965-09 L2	FX -SC08-G2-CT4PJ	4052899464858
LF1100TW-G5 -927.965-09 L2	FX-QMS-G1 -TU16H12LS-300	4052899449046
LF1100TW-G5 -927.957-09 L2	CORNER-FLEX -4P-003 KIT 10PCS	4062172179638
LF1100TW-G5 -927.957-09 L2	CORNER-FLEX -4P-015 KIT 10PCS	4062172179676
LF1100TW-G5 -927.957-09 L2	CONN-FLEX -3P-050 KIT 10PCS	4062172179690
LF1100TW-G5 -927.957-09 L2	CONN-FLEX -3P-200 KIT 10PCS	4062172179720
LF1100TW-G5 -927.957-09 L2	LTS-SLIMTRACK -2000 KIT 5 PCS	4062172207300
LF1100TW-G5 -927.957-09 L2	FX-QMS-G1 -TU15H6-300	4052899448865
LF1100TW-G5 -927.957-09 L2	FX-QMS-G1 -TU15H6W3-300	4052899448889
LF1100TW-G5 -927.957-09 L2	FX-QMS-G1 -TU16H12W3-300	4052899448988
LF1100TW-G5 -927.957-09 L2	FX-QMS-G1 -TU16H12-300	4052899448964
LF1100TW-G5 -927.957-09 L2	FX -SC08-G2-CT4PJ	4052899464858
LF1100TW-G5 -927.957-09 L2	FX-QMS-G1 -TU16H12LS-300	4052899449046
LF1100TW-G5 -925.940-09 L2	CORNER-FLEX -4P-003 KIT 10PCS	4062172179638
LF1100TW-G5 -925.940-09 L2	CORNER-FLEX -4P-015 KIT 10PCS	4062172179676
LF1100TW-G5 -925.940-09 L2	CONN-FLEX -3P-050 KIT 10PCS	4062172179690
LF1100TW-G5 -925.940-09 L2	CONN-FLEX -3P-200 KIT 10PCS	4062172179720
LF1100TW-G5 -925.940-09 L2	LTS-SLIMTRACK -2000 KIT 5 PCS	4062172207300
LF1100TW-G5 -925.940-09 L2	FX-QMS-G1 -TU15H6-300	4052899448865
LF1100TW-G5 -925.940-09 L2	FX-QMS-G1 -TU15H6W3-300	4052899448889
LF1100TW-G5 -925.940-09 L2	FX-QMS-G1 -TU16H12W3-300	4052899448988
LF1100TW-G5 -925.940-09 L2	FX-QMS-G1 -TU16H12-300	4052899448964

© 2024, Inventronics GmbH. Wszelkie prawa zastrzeżone. Inventronics jest licencjobiorcą marki OSRAM. OSRAM jest znakiem towarowym firmy ams OSRAM.

LF1100TW-G5 -925.940-09 L2	FX -SC08-G2-CT4PJ	4052899464858
LF1100TW-G5 -925.940-09 L2	FX-QMS-G1 -TU16H12LS-300	4052899449046
LF1100TW-G5 -922.935-09 L2	CORNER-FLEX -4P-003 KIT 10PCS	4062172179638
LF1100TW-G5 -922.935-09 L2	CORNER-FLEX -4P-015 KIT 10PCS	4062172179676
LF1100TW-G5 -922.935-09 L2	CONN-FLEX -3P-050 KIT 10PCS	4062172179690
LF1100TW-G5 -922.935-09 L2	CONN-FLEX -3P-200 KIT 10PCS	4062172179720
LF1100TW-G5 -922.935-09 L2	LTS-SLIMTRACK -2000 KIT 5 PCS	4062172207300
LF1100TW-G5 -922.935-09 L2	FX-QMS-G1 -TU15H6-300	4052899448865
LF1100TW-G5 -922.935-09 L2	FX-QMS-G1 -TU15H6W3-300	4052899448889
LF1100TW-G5 -922.935-09 L2	FX-QMS-G1 -TU16H12W3-300	4052899448988
LF1100TW-G5 -922.935-09 L2	FX-QMS-G1 -TU16H12-300	4052899448964
LF1100TW-G5 -922.935-09 L2	FX -SC08-G2-CT4PJ	4052899464858
LF1100TW-G5 -922.935-09 L2	FX-QMS-G1 -TU16H12LS-300	4052899449046

Oświadczenie

Zastrzega się możliwość zmian bez uprzedzenia. Błędy i ominięcia są możliwe. Należy zawsze upewnić się czy korzystasz z najnowszej wersji katalogu.

© 2024, Inventronics GmbH. Wszelkie prawa zastrzeżone. Inventronics jest licencjobiorcą marki OSRAM. OSRAM jest znakiem towarowym firmy ams OSRAM.