

HMI Double End Lamps




Areas of application

- Studio, TV, & Film
- Professional & High Speed Photography
- Solar Simulation


Product features and benefits

- High intensity light providing true color performance with CRI up to >90
- Color temperature approximately 6000 K - simulates daylight
- Robust design provides durability during transport
- High energy efficiency providing up to 100 lumens/watt
- Capable of hot restrike ignition
- Broad spectrum suitable for solar simulation applications
- High energy efficiency providing up to 100 lm/W
- Compression sealed base provides enhanced durability







HMI 6000W/ DXS



HMI 12000W/ DXS



HMI 18000W/ DXS



HMI 24000W/ DXS

Product family datasheet

Technical data

Product description	General Product Information			
	Product number (Americas)	Product name (Americas)	Family brand	Lamp type
HMI 575 W/DXS	54313	HMI 575W/DXS 10/CS 1/SKU	HMI	DOUBLE ENDED
HMI 1200 W/DXS	55139	HMI 1200W/DXS 10/CS 1/SKU	HMI	
HMI 2500 W/S XS	54068	HMI 2500W/S/XS 1/CS 1/SKU	HMI	
HMI 2500 W/DXS	54265	HMI 2500W/DXS 1/CS 1/SKU	HMI	
HMI 4000 W/DXS	54314	HMI 4000W/DXS 1/CS 1/SKU	HMI	
HMI 6000 W/DXS	54315	HMI 6000W/DXS 1/CS 1/SKU	HMI	
HMI 12000 W/DXS	54316	HMI 12000W/DXS 1/CS 1/SKU	HMI	ROUNDFOIL
HMI 4000 W/DXS SOLAR	56783	HMI4000WDXS SOLA R 1/CS 1/SKU		
HMI 18000 W/DXS	54213	HMI 18000W/DXS 1/CS 1/SKU	HMI	
HMI 24000 W/DXS	54325	HMI 24000W/DXS 1/CS 1/SKU	HMI	

Product description	Global order reference	Electrical Data		
		Nominal wattage	Nominal voltage	Nominal current
HMI 575 W/DXS	HMI 575 W/DXS	575 W	95 V	7 A
HMI 1200 W/DXS	HMI 1200 W/DXS	1200 W	100 V	13.8 A
HMI 2500 W/S XS	HMI 2500 W/S XS	2500 W	115 V	25.6 A
HMI 2500 W/DXS	HMI 2500 W/DXS	2500 W	115 V	25.6 A
HMI 4000 W/DXS	HMI 4000 W/DXS	4000 W	200 V	24 A
HMI 6000 W/DXS	HMI 6000 W/DXS	6000 W	122 V	55 A
HMI 12000 W/DXS	HMI 12000 W/DXS	12000 W	240 V	84 A
HMI 4000 W/DXS SOLAR	HMI 4000 W/DXS SOLAR	4000 W	200 V	24 A
HMI 18000 W/DXS	HMI 18000 W/DXS	18000 W	225 V	79 A
HMI 24000 W/DXS	HMI 24000 W/DXS	24000 W	280 V	90 A

Product description	Photometric Data	Physical Attributes & Dimensions		
	Nominal luminous flux	Lamp base	Diameter	Diameter
HMI 575 W/DXS	49000 lm	SFc10-4	21.0 mm	21.0 mm
HMI 1200 W/DXS	110000 lm	SFc15.5	27.0 mm	27.0 mm
HMI 2500 W/S XS	240000 lm	SFa21-12	31.5 mm	31.5 mm
HMI 2500 W/DXS	240000 lm	SFa21	31.5 mm	31.5 mm
HMI 4000 W/DXS	380000 lm	SFa21	36.0 mm	36.0 mm

Product family datasheet

Product description	Photometric Data	Physical Attributes & Dimensions		
	Nominal luminous flux	Lamp base	Diameter	Diameter
HMI 6000 W/DXS	570000 lm	S25.5	54.0 mm	54.0 mm
HMI 12000 W/DXS	1150000 lm	S30	64.0 mm	64.0 mm
HMI 4000 W/DXS SOLAR	395000 lm	SFa21-12	36.0 mm	36.0 mm
HMI 18000 W/DXS	1700000 lm	S30	70.0 mm	70.0 mm
HMI 24000 W/DXS	2300000 lm	S30	83.0 mm	83.0 mm

Product description	Diameter (in)	Length	Length with base excl. base pins/connection	Product weight
HMI 575 W/DXS	0.827 in	135.0 mm	115.00 mm	33.00 g
HMI 1200 W/DXS	1.063 in	220.0 mm	180.00 mm	104.00 g
HMI 2500 W/S XS	1.260 in	210.0 mm	150.00 mm	150.00 g
HMI 2500 W/DXS	1.260 in	355.0 mm	290.00 mm	196.00 g
HMI 4000 W/DXS	1.417 in	405.0 mm	340.00 mm	228.00 g
HMI 6000 W/DXS	2.126 in	450.0 mm		511.00 g
HMI 12000 W/DXS	2.520 in	470.0 mm		930.00 g
HMI 4000 W/DXS SOLAR		405.0 mm	340.00 mm	185.00 g
HMI 18000 W/DXS	2.756 in	500.0 mm		1000.00 g
HMI 24000 W/DXS	3.268 in	500.0 mm		1100.00 g

Product description	Electrode gap (cold)	Connector: presence	Operating Conditions	
			Burning position	Cooling
HMI 575 W/DXS			Any	
HMI 1200 W/DXS			Any	
HMI 2500 W/S XS			Other	
HMI 2500 W/DXS	14.0 mm		Other	Convection
HMI 4000 W/DXS	34.0 mm		p15	Convection
HMI 6000 W/DXS		Yes	p15	
HMI 12000 W/DXS		Yes	p15	
HMI 4000 W/DXS SOLAR			p15	
HMI 18000 W/DXS	44.0 mm	Yes	p15	Convection
HMI 24000 W/DXS		Yes	p15	Convection

Product description	Maximum permitted ambient temperature at base	Lifetime Data	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
		Nominal lifetime	Primary article identifier	Declaration no. in SCIP database
HMI 575 W/DXS		1000 hr	4008321285102	No declarable substances contained
HMI 1200 W/DXS		1000 hr	4008321931153	No declarable substances contained
HMI 2500 W/S XS		500 hr	4050300025780	No declarable substances contained

Product family datasheet

		Lifetime Data	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Product description	Maximum permitted ambient temperature at base	Nominal lifetime	Primary article identifier	Declaration no. in SCIP database
HMI 2500 W/DXS	450 °C	500 hr	4008321182197	No declarable substances contained
HMI 4000 W/DXS	450 °C	500 hr	4008321210203	No declarable substances contained
HMI 6000 W/DXS		500 hr	4008321210210	473650a6-c144- 4760-a4f0- 5f7779e0d7fe
HMI 12000 W/DXS		500 hr	4008321210227	9bbbe108-6929- 4ec2-90c3- f2313bf610cc
HMI 4000 W/DXS SOLAR		500 hr	4052899152601	No declarable substances contained
HMI 18000 W/DXS		500 hr	4008321370280	f14371f4-413d-4982- a113-e8e17de542e0
HMI 24000 W/DXS		375 hr	4008321355805	e6c82c15-550e- 4821-97a3- 8abf917baea6

Product description	Candidate list substance 1	CAS No. of substance 1	Safe use instruction
HMI 575 W/DXS	No declarable substances contained		
HMI 1200 W/DXS	No declarable substances contained		
HMI 2500 W/S XS	No declarable substances contained		
HMI 2500 W/DXS	No declarable substances contained		
HMI 4000 W/DXS	No declarable substances contained		
HMI 6000 W/DXS	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.
HMI 12000 W/DXS	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.
HMI 4000 W/DXS SOLAR	No declarable substances contained		

Product family datasheet

Product description	Candidate list substance 1	CAS No. of substance 1	Safe use instruction
HMI 18000 W/DXS	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.
HMI 24000 W/DXS	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.

Product family datasheet

Safety advice

Because of their high luminance, UV radiation and high internal pressure during operation, HMI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.