

XENARC COOL BLUE BOOST

Hyper white light for LED look for off-road use



Xenon hyper white light for stylish LED look

Hyper white light due to a special filling system instead of conventional coating



Up to 7,000 K¹⁾

High contrast and most stylish look



Enhanced brightness

More light allows to see farther and therefore react sooner



Hyper white light with up to 7,000 K for off-road use

XENARC COOL BLUE BOOST features hyper white xenon light for LED look and high color temperatures of up to 7,000 K. This is due to a special filling system instead of conventional coating. The lamps generate enhanced brightness. These products do not have ECE approval. This means they must not be used on public roads in any exterior application. Use on public roads leads to cancellation of operating license and loss of insurance coverage. Several countries do not allow sale and use of these products. Please contact your local distributor for information on the availability in your country.

¹⁾ Measured in headlamps

Product family datasheet

Technical data

Product description	Electrical Data					Photometric Data
	Power input	Nominal voltage	Nominal wattage	Power input tolerance	Test voltage	Nominal luminous flux
XENARC COOL BLUE BOOST \triangleq D1S	35 W	85 V	35 W	$\pm 3 \%$	13.5 V	3200 lm
XENARC COOL BLUE BOOST \triangleq D2S	35 W	85 V	35 W	$\pm 3 \%$	13.5 V	3200 lm
XENARC COOL BLUE BOOST \triangleq D3S	35 W	42 V	35 W	$\pm 3 \%$	13.5 V	3200 lm
XENARC COOL BLUE BOOST \triangleq D4S	35 W	42 V	35 W	$\pm 3 \%$	13.5 V	3200 lm

Product description	Luminous flux tolerance	Physical Attributes & Dimensions		
		Lamp base	Length	Diameter
XENARC COOL BLUE BOOST \triangleq D1S	$\pm 15 \%$	PK32d-2	83.2 mm	9 mm
XENARC COOL BLUE BOOST \triangleq D2S	$\pm 15 \%$	P32d-2	77.3 mm	9 mm
XENARC COOL BLUE BOOST \triangleq D3S	$\pm 15 \%$	PK32d-5	83.2 mm	9 mm
XENARC COOL BLUE BOOST \triangleq D4S	$\pm 15 \%$	P32d-5	77.3 mm	9 mm

Product description	Diameter	Lifetime Data		Capabilities	Certificates & standards	Environmental & Regulatory Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
		Lifespan B3	Lifespan Tc	Technology	ECE category	Primary article identifier
XENARC COOL BLUE BOOST \triangleq D1S	9 mm	600 hr	1500 hr	HID	- ¹⁾	4052899439184 4062172404129
XENARC COOL BLUE BOOST \triangleq D2S	9 mm	600 hr	1500 hr	HID	- ¹⁾	4062172404150 4052899441026
XENARC COOL BLUE BOOST \triangleq D3S	9 mm	1000 hr	1500 hr	HID	- ¹⁾	4052899527560 4062172404181
XENARC COOL BLUE BOOST \triangleq D4S	9 mm	1000 hr	1500 hr	HID	- ¹⁾	4052899527522

Product description	Candidate list substance 1	CAS No. of substance 1	Safe use instruction	Declaration no. in SCIP database
XENARC COOL BLUE BOOST \triangleq D1S	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	510b3515-af3b-4ebb-93d3-c9dd67e73c84 4a196424-fbe4-4fd5-8eb2-6dfb70acf828

Product family datasheet

Product description	Candidate list substance 1	CAS No. of substance 1	Safe use instruction	Declaration no. in SCIP database
XENARC COOL BLUE BOOST ≙ D2S	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	6c57c564-b94d-41ad-aafc-6dd568694c25
XENARC COOL BLUE BOOST ≙ D3S	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	52eaf09b-051b-4888-b1fc-0e5b2b78b12f 339d84e0-b5c1-49b0-814c-94cae2e6e2fc
XENARC COOL BLUE BOOST ≙ D4S	No declarable substances contained			No declarable substances contained

1) To be operated only with approved electronic control gear

Download Data

File	
	User instruction GPRS_Safety symbols instructions
	ref_pim_amsproduct360degreeimages XENARC COOL BLUE BOOST D1S 66140CBB
	ref_pim_amsproduct360degreeimages XENARC COOL BLUE BOOST OFFROAD D2S 66240CBB
	ref_pim_amsproduct360degreeimages XENARC COOL BLUE BOOST OFFROAD D3S 66340CBB
	ref_pim_amsproduct360degreeimages XENARC COOL BLUE BOOST OFFROAD D4S 66440CBB

Safety advice

XENARC lamp change is recommended to be carried out by a professional. This product must only be operated with approved electronic control gear.

Legal advice

*These products do not have ECE approval. This means they must not be used on public roads in any exterior application. Use on public roads leads to cancellation of operating license and loss of insurance coverage. Several countries do not allow sale and use of these products. Please contact your local distributor for information on the availability in your country.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

