

HMI DIGITAL 18000 W

HMI DIGITAL | Lampy metalohalogenkowe, jednotrzonkowe



Obszar zastosowań

- Studio
- Stage
- TV

Korzyści ze stosowania produktu

- Suited for both analog and digital film production
- Robust stems, resulting in less breakage during transport
- Round moly-foil construction that evenly distributes heat and current extends for lamp longevity (6,000-18,000 W)
- Splash-proof carrying case is re-usable and allows lamps to be transported safely (6,000-18,000 W)

Cechy produktu

- High CRI of >90
- UV-Stop (UVS)
- Color temperature of 6,000 K (daylight)
- Extremely bright light of up to 100 lumens/watt
- Zdolność do „gorącego restartu”



Dane techniczne

Dane elektryczne

Moc znamionowa	1800000 W
Napięcie nominalne	225 V
Prąd znamionowy	88 A

Dane fotometryczne

Znamionowy strumień świetlny	1600000 lm
Temperatura barwowa	6000 K
Ogólny wskaźnik oddawania barw Ra	95

Wymiary i waga

Średnica	1000 mm
Długość	4950 mm

Trwałość

Trwałość	300 h
----------	-------

Dodatkowe dane produktu

Trzonek (standardowe rozwiązanie)	GX51
-----------------------------------	------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	06-03-2024
Primary Article Identifier	4062172123372
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	0fcb88f6-5cad-4934-b467-37465d62c7d2

Karta katalogowa produktu

Instrukcja bezpieczeństwa

Because of their high luminance, UV radiation and high internal pressure during operation, HMI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Dane logistyczne

Kod produktu	Opis produktu	Opakowanie (liczba produktów / opakowanie)	Wymiary (długość x szerokość x wysokość)	Objętość	Waga brutto
4062172123372	HMI DIGITAL 18000 W	Karton wysyłkowy 1	400 mm x 400 mm x 900 mm	144.00 dm ³	5517.00 g

Wymieniony kod produktu oznacza najmniejszą ilość produktu, jaka może być zamówiona. Jednostka transportowa może zawierać jedną sztukę lub więcej. Składając zamówienie prosimy o zamawianie ilości odpowiadających jednej lub wielokrotności jednostki transportowej.

Oświadczenie

Zastrzega się możliwość zmian bez uprzedzenia. Błędy i ominięcia są możliwe. Należy zawsze upewnić się czy korzystasz z najnowszej wersji katalogu.