

## GFDS400TW-G1-82757- -01

GINOLED Flex DIFFUSE Side-Tunable White | Moduły LED do zastosowań profesjonalnych w przemyśle



### Cechy produktu

- Available for 2700 K to 5700 K CCT adjustable
- 3 SDCM, CRI80
- IP65 protection for indoor and semi-outdoor application
- 110° viewing angle per module
- Up to 50,000 hrs lifetime @ tc max

### Korzyści ze stosowania produktu

- 10x9 mm super slim design, fit for embedded applications
- Diffuse version, side emitting, High uniformity without hot spot and dark area
- Customization length to meet customer difference length requirements

### Obszar zastosowań

- Hotele
- Oświetlenie reklamowe
- Oświetlenie fasad budynków
- Integracja ścienna



### Dane techniczne

#### Dane elektryczne

Napięcie nominalne	24,0 V
Rodzaj prądu	DC
Moc znamionowa	6,00 W
Zakres napięcia wejściowego	23...25 V
Accidental reverse input voltage protection up to	25 V

#### Dane fotometryczne

Barwa światła LED	Przestrajalne Białe
Temperatura barwowa	2700 K
Ogólny wskaźnik oddawania barw Ra	80
Strumień świetlny na metr	820 lm
Całkowity użyteczny strumień świetlny	820 lm
Skuteczność świetlna	67 lm/W
Standardowe odchylenie dopasowania barw	≤3 sdc


#### Dane świetlne

LED pitch	3.57 mm
Kąt rozsyłu światła	110 °
Znamionowy kąt rozsyłu (kąt użyteczny)	110,00 °
Czas startu	< 0,5 s
Czas startu (60 %)	< 0,50 s

#### Dane o module LED

Liczba LED na metr	280
Liczba LED w najmniejszej jedn. podziału	14

## Wymiary i waga



<b>Długość</b>	1000,0 mm
<b>Długość - najmniejszej jedn. podziału</b>	50,0 mm
<b>Szerokość</b>	9,00 mm
<b>Wysokość</b>	10,00 mm
<b>Długość przewodów</b>	380,0
<b>Masa produktu</b>	120,00 g
<b>Przekrój przewodu, strona wejściowa</b>	0.32 mm <sup>2</sup>

## Kolory i materiały

<b>Materiał osłony</b>	Silicone
<b>Materiał</b>	Silicone

## Temperatury i warunki pracy

<b>Wydajność temperaturowa wg IEC 62717</b>	35 °C
<b>Zakres temperatury pracy</b>	-25...65 °C <sup>1)</sup>
<b>Zakres temperatury otoczenia</b>	-25...+45 °C
<b>Zakres temperatury magazynowania</b>	-25...80 °C

<sup>1)</sup> Exceeding the maximum ratings will reduce expected life time or destroy the LED strip.

## Trwałość

<b>Trwałość</b>	50000 h
<b>Znamionowa trwałość</b>	50000 h
<b>Wsp. zachowania str. świetlnego</b>	0,70
<b>Liczba cykli włączeniowych</b>	15000

## Dodatkowe dane produktu

<b>ID of contained light source</b>	LS_SHZ_600872
-------------------------------------	---------------

## Karta katalogowa produktu

### Możliwości

Ściemnianie	Tak
Lowest bending radius	60 mm

### Certyfikaty i Normy

Zużycie energii	14 kWh/1000h
Normy	Acc. to EN62471/EN62778/ISO 4892-2 - Method A/IEC 60068-2-52 severity 1/RoHS/Reach/CE/IEC60068-2-60 Test Ke Method 4
Typ zabezpieczenia	IP65
Energy efficiency class of the contained light source	E





### Dane logistyczne

Kod taryfy celnej	940542319000
-------------------	--------------

### Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (RECh)	
Date of Declaration	30-12-2021
Primary Article Identifier	4062172147453
Candidate List Substance 1	No declarable substances contained
CAS No. of substance 1	No CAS
Declaration No. in SCIP database	No declarable substances contained

### Pobierz dane

Plik	
	User instruction GinoLED Flex Diffuse Side Tunable White
	Dodatkowe informacje techniczne GFDS TW - Specification sheet
	Deklaracje zgodności GFD TW CE 4237513 040221
	IES data GFDS400TW-G1-82757-0105

## Karta katalogowa produktu

### Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer. In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

### Dane logistyczne

Kod produktu	Opis produktu	Opakowanie (liczba produktów / opakowanie)	Wymiary (długość x szerokość x wysokość)	Objętość	Waga brutto
4062172147453	GFDS400TW-G1-82757- - 01	Karton wysyłkowy 40	570 mm x 570 mm x 380 mm	123.46 dm <sup>3</sup>	12740.00 g

Wymieniony kod produktu oznacza najmniejszą ilość produktu, jaka może być zamówiona. Jednostka transportowa może zawierać jedną sztukę lub więcej. Składając zamówienie prosimy o zamawianie ilości odpowiadających jednej lub wielokrotności jednostki transportowej.

### Oświadczenie

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.