OSRAM

LEDriving SL W5W RED

Ideal replacement for any vehicle



Suitable for various vehicle exterior applications

Available in Red



Replaces conventional W5W lamps

Easy upgrade to LED technology with plug & play solutions



Reliable OSRAM quality stands for less lamp replacements

4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for W5W

LEDriving SL W5W replacement lamps offer a modern and intense light. These replacement lamps are suitable for all conventional W5W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

| | Product information | | General Product Information | | Electrical Data | |
|---------------------|--|---|--------------------------------|----------|--------------------|----------------------------------|
| Product description | Application (Category and Product specific) | Product type (off- road vs. on-road) | Global referen | | Power input | Nominal voltage |
| LEDriving SL ≙ W5W | Mainly used for signal/ indicator/ interior applications | Off-road ≙ W5W | 2825DRP | | 0.8 W 12 V | |
| | | | Photometric Data | | | Physical Attributes & Dimensions |
| Product description | Nominal wattage | Test voltage | Nominal flux | luminous | Luminous flux | Diameter |
| | | | | | tolerance | |
| LEDriving SL ≙ W5W | 1 W | 13.5 V | 15 lm | | tolerance ±25 % | 10.0 mm |

| Product description | Candidate list substance 1 | CAS No. of substance | Safe use instruction | Declaration no. in SCIP database |
|---------------------|----------------------------|----------------------|--|--|
| LEDriving SL ≜ W5W | Lead | 7439-92-1 | The identification of the Candidate List substance is sufficient to allow safe use of the article. | 1c4e9be1-c3b2- 4d06-8a9b- ac63609c2e8a d820726e-410f-45f9- 9fb7-5f106598c292 |

Lifespan

1500 hr

Lifespan

4000 hr

Tc

Technology

LED 1)

Primary article identifier

4062172150316 | 4062172401692

Diameter

10.0 mm

Product description

 $^{^{1)}}$ Light-emitting diode lamp

Product family datasheet

Download Data

File



User instruction

GPRS_Safety symbols instructions



Brochures

LEDriving Retrofits - Exchange overview (EN)

Safety advice

Canbus compatibleColoured lamps for usage behind coloured glass

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.