

# TYREinflate 1000



## Rapid Inflation Time

Inflate the tire to the desired pressure in ca. 2 minutes\*\*



## Wind-up Cable

Winding/unwinding mechanism for a neatly rolled up cable



## LED Light

Easy to operate even in darkness and in low light conditions



### Rapid tyre inflator with wind-up cable

The OSRAM Tyreinflate 1000 is a rapid digital tyre inflator with a backlit digital display for easy, accurate pressure readings. Includes an auto stop feature to get the exact desired pressure needed to accurately inflate your tyres. The auto set on the Tyreinflate 1000 is incredibly easy to set up - just turn the dial to the pressure you require, click to set, then press start. The inflator will automatically stop once the correct pressure has been reached.

A wind-up power cable eliminates messy wires and a 2 minute inflation time\* gets you on the road and where you need to be quickly. The power cable is long enough (3.5 m) to reach all tyres around your vehicle.

The large on/off button and the LED directional light make the Tyreinflate 1000 easy to use in darkness and emergencies – keeping you prepared for whatever may happen on the road.

Includes 3-piece adaptor for bicycles, balls and other inflatables.












\*\*based on inflating a 13" tyre from flat to 2.41 BAR

Product family datasheet

Technical data

Product description	General Product Information	Electrical Data	Physical Attributes & Dimensions	
	Global order reference	Nominal voltage	Height	Width
TYRE inflate 1000	OTI1000	11.1 V	219.0 mm	88.0 mm
Product description	Length	Operating Conditions	Additional product data	Capabilities
		Noise Level (dB)	Display Type	Fuse
TYRE inflate 1000	200.0 mm	90 dB	Digital	15 A
Product description	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)			
	Candidate list substance 1	CAS No. of substance 1	Safe use instruction	Declaration no. in SCIP database
TYRE inflate 1000	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	166a46e8-51b1-466f-9cfd-6a1cc6989c16   b0abf529-311b-4f43-8c8e-139c08188c8b

Download Data

File	
	User instruction TYREinflate 1000
	Movie application OSRAM TYREinflate 1000 Application Video Short (EN)
	Movie application OSRAM TYREinflate 1000 Application Video Short (DE)
	Movie application TyreInflate How to Video (RU)
	Product movie TyreInflate How to Video (EN)
	Product movie TyreInflate How to Video (IT)
	Product movie TyreInflate 1000 Product Video (RU)
	Product movie TyreInflate 1000 Product Video (EN)
	Product movie TyreInflate 1000 Product Video (ITA)
	Video OSRAM TYREinflate 1000: Rapid tyre inflator with wind-up cable, large digital display and LED light
	Video OSRAM TYREinflate How To: Change your vehicle's tyre pressure easily

Safety advice

Product won't exceed noise levels of more than 90 dB

Legal advice

CE and EAC compliant

\* for precise conditions please refer to: [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)

\*\* based on inflating a 13" tyre from flat to 2.41 BARApplication advice:

For more detailed application information and graphics please see product datasheet.

Disclaimer:

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.