

TF400RGB -G1-05

TEC FLEX Colormix IP00 | LED modules flexible, strips, colored



Cechy produktu

- Elastyczna taśma i taśma LED z możliwością przycinania
- Up to 50,000 hrs lifetime @ tc max

Korzyści ze stosowania produktu

- Równomierna zmiana kolorów
- Łatwy montaż na wielu delikatnych powierzchniach dzięki taśmie samoprzylepnej z tyłu

Obszar zastosowań

- Oświetlenie efektowe w architekturze



Dane techniczne


Dane elektryczne

Napięcie nominalne	24,0 V
Rodzaj prądu	DC
Moc znamionowa	48,50 W
Zakres napięcia wejściowego	23...25 V
Accidental reverse input voltage protection up to	25 V

Dane fotometryczne

Barwa światła LED	RGB
Skuteczność świetlna	33,3 lm/W
Barwa światła (oznaczenie)	Czerwony/Zielony/Niebieski
Strumień świetlny na metr	380 lm

Wymiary i waga



Długość	5000,0 mm
Masa produktu	65,00 g
Przekrój przewodu, strona wejściowa	0,5 mm ²
Szerokość	8,00 mm
Wysokość	1,50 mm

Temperatury i warunki pracy

Zakres temperatury pracy	-25...80 °C
Zakres temperatury magazynowania	-30...85 °C

Dodatkowe dane produktu

ID of contained light source [AGGR]	LS_SHZ_600468
-------------------------------------	---------------

Karta katalogowa produktu

Certyfikaty i Normy

Energy efficiency class of the contained light source	G
---	---

Dane logistyczne

Kod taryfy celnej	85395100000
-------------------	-------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	07-07-2023
Primary Article Identifier	4062172154284
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	610b9928-cf09-4dc4-9282-a76db081ba4d

Wyposażenie / Akcesoria

- Uprozczone połączenie z dopasowanym systemem CONNECTsystem jako opcja



TEC Flex RGB IP00

Pobierz dane

Plik	
	User instruction TEC Flex Tunable White, TEC Flex RGB

Karta katalogowa produktu

	Product Datasheet TEC Flex RGB IP00 Product Datasheet, EN
	Broszury Light is strong - Discover the versatile and flexible lighting system OSRAM 24V TEC Flex (EN)
	Certyfikaty TEC Flex RGB CE 4239858 210820
	Certyfikaty TF(P)RGB ENEC 35-115144 140920
	Eulumat Eulumat TF400RGB-LDT
	IES data Eulumat TF400RGB-IES

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015. The contained light source is intended for use in applications requiring high-quality coloured light.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer. In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Dane logistyczne

Kod produktu	Opis produktu	Opakowanie (liczba produktów / opakowanie)	Wymiary (długość x szerokość x wysokość)	Objętość	Waga brutto
4062172154284	TF400RGB -G1-05	Karton wysylkowy 10	225 mm x 240 mm x 120 mm	6.48 dm ³	1304.00 g

Wymieniony kod produktu oznacza najmniejszą ilość produktu, jaka może być zamówiona. Jednostka transportowa może zawierać jedną sztukę lub więcej. Składając zamówienie prosimy o zamawianie ilości odpowiadających jednej lub wielokrotności jednostki transportowej.

Karta katalogowa produktu

Akcesoria opcjonalne

Opis produktu	Nazwa akcesorium	Kod akcesorium
TF400RGB -G1-05	CORNER-FLEX -4P-003 KIT 10PCS	▶ 4062172179638
TF400RGB -G1-05	CORNER-FLEX -4P-015 KIT 10PCS	▶ 4062172179676
TF400RGB -G1-05	CONN-FLEX -4P-050 KIT 10PCS	▶ 4062172179744
TF400RGB -G1-05	CONN-FLEX -4P-200 KIT 10PCS	▶ 4062172179768
TF400RGB -G1-05	LTS-SLIMTRACK -2000 KIT 5 PCS	▶ 4062172207300
TF400RGB -G1-05	FX-QMS-G1 -TU15H6-300	▶ 4052899448865
TF400RGB -G1-05	FX-QMS-G1 -TU15H6W3-300	▶ 4052899448889
TF400RGB -G1-05	FX-QMS-G1 -TU16H12W3-300	▶ 4052899448988
TF400RGB -G1-05	FX-QMS-G1 -TU16H12-300	▶ 4052899448964
TF400RGB -G1-05	FX -SC08-G2-CT4PJ	▶ 4052899464858
TF400RGB -G1-05	FX-QMS-G1 -TU16H12LS-300	▶ 4052899449046

Oświadczenie

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.