# **OSRAM**

## Round VX80-WD



**ECE certified - ECE R112** 

The necessary tests and approvals were carried out and an ECE type approval was granted <sup>2)</sup>ECE reference number: 12.5



**Wide Beam** 

Designed for a near field illumination. For large area illumination in the near field of the vehicle



Light beam up to 240 m length

See and be seen with OSRAM



On-road & Off-road

Versatile applicable and flexible in use.On-road & off-road, in terrain, at work and in the spare time.



## Bringing light to life with OSRAM LEDriving driving and working lights

Considerable foresight on dark country roads, forest paths, off the beaten tracks, off-road and on-road- this can be achieved with the OSRAM LEDriving Round VX80-WD. With its 4 powerful, high-performance long-life LEDs, the OSRAM LEDriving Round VX80-WD has a range of up to 240 meters and thus offers the driver impressive foresight on-road and off-road. Even in dim light and reduced visibility due to external environmental influences, the OSRAM LEDriving Round VX80-WD with up to 6000 Kelvin can provide conditions similar to daylight. The power package with up to 1150 lumens of luminosity scores with highest optical efficiency and homogeneous light distribution. This results in the possibility of an improved view for you and the improved visibility of your vehicle by other road users, and consequently also increased safety on-road and off-road. Whether on-road or off-road - The OSRAM LEDriving Round VX80-WD impresses with its powerful performance and a long service life with up to 5000 hours. Versatile applicable, it defies numerous environmental influences and, thanks to high-quality materials such as the aluminum housing and the stable polycarbonate lens, it is particularly light and at the same time robust and resistant. The OSRAM LEDriving Round VX80-WD has been tested and validated with the IP-Protection Class IP67 in our DIN certified environmental simulation laboratory for extreme external influences regarding water, dust, impacts, heat,

cold and permanent vibration. The integrated driver and the thermal management system regulate the temperature of the OSRAM LEDriving Round VX80-WD and can thus prevent damage from overheating. The polarity protection inhibits the wrong polarity of the voltage supply and can thus prevent possible damage by automatically switching off the LEDs. On-road and off-road, the OSRAM LEDriving Round VX80-WD is an effective and efficient addition to your vehicle. No registration or entry in the vehicle documents is necessary for these ECE-certified LED driving lights<sup>2)</sup>.

ECE reference number: 12.5

The OSRAM LEDriving Round VX80-WD can be attached to cars, trucks, agricultural machinery, farm machinery, commercial vehicles, construction vehicles, caravans, offroad vehicles and quads<sup>2)</sup>.

The OSRAM LEDriving Round VX80-WD is versatile applicable and flexible in use.

2) OSRAM LEDriving Driving Lights are approved according to ECE regulations and may therefore be installed and operated on public roads. Please note: Special installation regulations apply. In addition to ECE approval of the product, individual special requirements and legislation of the countries must be observed.

## Technical data

	scription Application (Category G			General Product Information		Electrical Data			
Product description			Global order reference		Nominal voltage		•	Nominal wattage	
Round VX80-WD 1)	Additional high beam application		LEDDL119-WD		12/24 V			24 W	
		Photomet	ric Data	LED modu		Lifetime Data	Capa	bilities	
Product description	Test voltage	voltage flux L		Number of LEDs per module		Lifespan Tc	Technology		
Round VX80-WD 1)	13.5 V	1150 lm		4		5000 hr	LED	2)	
	Certificates	& standard	ls						
Product description	Approval ma			Type of protection		Standards		ECE reference number	
Round VX80-WD 1)	E4 approval		IP67		ECE R	10, R112		12.5	
	Logistical da	ata	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)						
Product description	Commodity	Commodity code		Candidate list substance 1		CAS No. of substance		Safe use instruction	
Round VX80-WD <sup>1)</sup>	8512200090	00	Lead		7439	9-92-1		The identification of the Candidate List substance is sufficient to allow safe use of the	

Product description	Declaration no. in SCIP database
Round VX80-WD 1)	6b936d75-46c3-
	4dde-882e-
	86058d6b5b22
	df0f295e-34cd-4286-
	b5ea-a2e1b687bbf3
	d24869ff-3230-4b0b-
	9125-9296f06e8a68

<sup>1)</sup> Beam Pattern: Wide

article.

 $<sup>^{2)}\, {\</sup>rm Light\text{-}emitting}\,\, {\rm diode}\,\, {\rm application}$ 

#### Download Data

	File
太	User instruction LEDriving Round VX80-WD
太	User instruction GPRS_Safety symbols instructions
	Movie application LEDriving D and W Image Video Bringing light to life (EN)
	Movie application Working and Driving Lights Amarok Winter
	Movie application LEDriving Driving and Working Lights Reference Video (EN)
	Movie application OSRAM LEDdriving and working lights Imagefilm (EN)
D	Movie application OSRAM Quality Testing LEDriving working and driving lights (EN)
O	Video Light is Quality -OSRAM LEDriving Driving and Working Lights Quality Tests (EN)
D	Video OSRAM LEDriving driving and working lights: The night doesn't stand a chance
D	Video OSRAM LEDriving driving and working lights in action - From on road to off road applications (EN)
D	Video Reference Number made easy - Making sure your LEDriving Driving Lights are legal on public roads
	ref_pim_amsp_product360degreeimages Round VX80-WD LEDDL119-WD

#### Legal advice

Legal advice:

The installation of the OSRAM LEDriving Round VX80-WD is fully ECE compliant and therefore registration free. This does not include individual custom requirements of countries, in addition to the standardized ECE certification of the product.

- 1) Precise terms and conditions at: www.osram.com/am-guarantee
- 2) OSRAM LEDriving Driving Lights are approved according to ECE regulations and may therefore be installed and operated on public roads. Please note: Special installation regulations apply. In addition to ECE approval of the product, individual special requirements and legislation of the countries must be observed.Refer to www.osram.com/am-guarantee for precise conditions

### **Application advice**

For more detailed application information and graphics please see product datasheet.

#### **Disclaimer**

Troduct family datasnect
Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.