

FX -SC08-G2-CT4PJ

Tunable White 3pin Flexible LED strips Connector | Accessories for Flexible LED strips

Cechy produktu

- Quick and easy installation
- Compatible with TEC Flex




Korzyści ze stosowania produktu

- Łatwa instalacja, nie jest wymagane lutowanie ani narzędzia (CONNECTsystem)
- Ograniczony czas instalacji (CONNECTsystem)
- Możliwość podłączenia z przodu modułu lub w miejscach odgałęzienia (CONNECTsystem)
- Niski profil (CONNECTsystem)

Dane techniczne

Wymiary i waga



Długość	9,0 mm
Masa produktu	0,80 g
Szerokość	9,2 mm
Wysokość	5,9 mm

Dane logistyczne

Kod taryfy celnej	85366990990
-------------------	-------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	30-08-2022
Primary Article Identifier	4052899464858
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	No declarable substances contained

Pobierz dane

Plik	
	User instruction Connection System for LINEARlight Flex & TEC Flex IP00
	Product Datasheet 726951_SLIMCONNECT SYSTEM 08 G2
	Broszury Light is freedom of design (EN)

Karta katalogowa produktu

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer. In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Dane logistyczne

Kod produktu	Opis produktu	Opakowanie (liczba produktów / opakowanie)	Wymiary (długość x szerokość x wysokość)	Objętość	Waga brutto
4052899464858	FX -SC08-G2-CT4PJ	Karton wysyłkowy 1250	510 mm x 340 mm x 315 mm	54.62 dm ³	3914.00 g

Wymieniony kod produktu oznacza najmniejszą ilość produktu, jaka może być zamówiona. Jednostka transportowa może zawierać jedną sztukę lub więcej. Składając zamówienie prosimy o zamawianie ilości odpowiadających jednej lub wielokrotności jednostki transportowej.

Oświadczenie

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.