

LEDDriving HL EASY H15



Ultra compact LED replacement for conventional H15 high and low beam lamps (2in1)

“Socket Design” – no adapters and caps needed



Easy plug & play installation

Allowing a high compatibility and an easy installation for an even wider range of car models.



Cool White color temperature

Better visibility thanks to daylight effect



LED high and low beams lamps with plug & play system: no adapters and caps needed.

With its socket-based solution, the OSRAM LEDDriving HL EASY retrofits provide an ultra-compact LED replacement of conventional H7/H18, H4/H19 and H15 high and low beam lamps with cool white LED light – providing a stylish look as well as superior brightness. It offers an easy plug & play installation with optimized compatibility: no adapters and caps needed! An optimized high-speed fan ensures active cooling – making a higher performance and high-level light output possible thanks to maximized heat dissipation.

The LEDDriving HL EASY high and low beam lamps by OSRAM replace conventional halogen lamps, are 12V compatible and have a cool white color temperature. With

the latest LED technology and very compact design, these lamps allow a high compatibility and an easy installation for cars with the respective halogen lamp types. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

Product description	Product information		General Product Information	Electrical Data	
	Product type (off-road vs. on-road)	Application (Category and Product specific)	Global order reference	Power input	Nominal voltage
LEDDriving HL EASY \triangleq H15	Off-road \triangleq H15	Mainly used for Low Beam, High Beam, Daytime running light, position lighting applications	64176DWESY	16.5 / 3.8 W	12 V

Product description	Test voltage	Photometric Data		Physical Attributes & Dimensions	
		Nominal luminous flux	Luminous flux tolerance	Diameter	Diameter
LEDDriving HL EASY \triangleq H15	13.2 V	1250/250 lm	$\pm 25\%$	15.8 mm	15.8 mm

Product description	Lifetime Data	Capabilities	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)		
	Lifespan Tc	Technology	Primary article identifier	Candidate list substance 1	CAS No. of substance 1
LEDDriving HL EASY \triangleq H15	1000 hr	LED	4062172294966 4062172398350 4062172312592	Lead	7439-92-1

Product description	Safe use instruction	Declaration no. in SCIP database
LEDDriving HL EASY \triangleq H15	The identification of the Candidate List substance is sufficient to allow safe use of the article.	71c142ec-374e-4388-9e54-b12e0eaecde1 454fe0c4-a884-4b8c-9105-1bd9044203c9 ee9bec0d-db20-4643-8e67-aa9e301fc3a5

Download Data

File	
	User instruction GPRS_Safety symbols instructions
	Brochures LEDiving Retrofits - Exchange overview (EN)

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

