

## LR-P-1500 -RGBW830-120DBK06IGG1L

LINEARlight Rigid FINESSE InGround



### Cechy produktu

- Slim, modular LED fixture for linear applications, fully customizable
- Several optics, Wall Grazing and WallWashing; 10°, 30°, 60°
- Outdoor IP67
- Luminous flux: > 2000 lm/m; 1200 m/m; 900 lm/m
- Color uniformity  $\leq 2$  SDCM
- Lifetime up to 60.000 h L80B10
- Large selection of lighting color temperatures

### Korzyści ze stosowania produktu

- 3 lengths available to adapt to different conditions
- External metal case available
- Easy to configure the desired light performance for optimal illumination
- Protected against the atmospheric agents: from the desert to the glacier
- Long-time functionality and maintenance-free
- High color fidelity to beautify every design
- Fully controllable by most used light control protocols: DALI, DMX
- Color consistent with LINEARlight FLEX products

### Obszar zastosowań

- Wall washing
- Wall Grazing
- Architectural integration



Dane techniczne

Dane elektryczne

|                                                   |           |
|---------------------------------------------------|-----------|
| Rodzaj prądu                                      | DC        |
| Accidental reverse input voltage protection up to | 25 V      |
| Zakres napięcia wejściowego                       | 23...25 V |

Dane fotometryczne

|                      |            |
|----------------------|------------|
| Skuteczność świetlna | 45 lm/W    |
| Temperatura barwowa  | 3000 K     |
| Barwa światła LED    | RGB, white |

Dane świetlne

|           |          |
|-----------|----------|
| LED pitch | 16.67 mm |
|-----------|----------|

Dane o module LED

|                                          |    |
|------------------------------------------|----|
| Liczba LED w module                      | 72 |
| Liczba LED w najmniejszej jedn. podziału | 72 |

Wymiary i waga



|                   |           |
|-------------------|-----------|
| Masa produktu     | 2350,00 g |
| Długość           | 676,0 mm  |
| Szerokość         | 61,5 mm   |
| Wysokość          | 62,0 mm   |
| Długość przewodów | 250,0     |

Temperatury i warunki pracy

|                                  |             |
|----------------------------------|-------------|
| Zakres temperatury magazynowania | -20...85 °C |
|----------------------------------|-------------|

Karta katalogowa produktu

Trwałość

|                         |         |
|-------------------------|---------|
| Related Lifetime L80B10 | 60000 h |
| Related Lifetime L90B10 | 60000 h |

Możliwości

|                     |     |
|---------------------|-----|
| With end piece      | Nie |
| With connection set | Nie |
| Self-adhesive       | Nie |

Certyfikaty i Normy

|       |         |
|-------|---------|
| Normy | CE/ENEC |
|-------|---------|

Dane logistyczne

|                   |             |
|-------------------|-------------|
| Kod taryfy celnej | 94051190900 |
|-------------------|-------------|

Environmental information

| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) |               |
|-----------------------------------------------------------------------|---------------|
| Date of Declaration                                                   | 02-12-2022    |
| Primary Article Identifier                                            | 4062172307765 |
| Declaration No. in SCIP database                                      | In work       |

Pobierz dane

| Plik                                                                                |                                                                             |
|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|
|  | User instruction<br>LINEARlight Rigid FINESSE In Ground                     |
|  | Product Datasheet<br>LINEARlight RIGID FINESSE InGround Specification Sheet |
|  | Broszury<br>Light is awesome - LINEARlight Rigid FINESSE (EN)               |

Karta katalogowa produktu

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer. In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Dane logistyczne

| Kod produktu  | Opis produktu                    | Opakowanie (liczba produktów / opakowanie) | Wymiary (długość x szerokość x wysokość) | Objętość              | Waga brutto |
|---------------|----------------------------------|--------------------------------------------|------------------------------------------|-----------------------|-------------|
| 4062172307765 | LR-P-1500 -RGBW830-120DBK06IGG1L | Karton wysyłkowy<br>1                      | 780 mm x 180 mm x 140 mm                 | 19.66 dm <sup>3</sup> | 2920.00 g   |

Wymieniony kod produktu oznacza najmniejszą ilość produktu, jaka może być zamówiona. Jednostka transportowa może zawierać jedną sztukę lub więcej. Składając zamówienie prosimy o zamawianie ilości odpowiadających jednej lub wielokrotności jednostki transportowej.

Oświadczenie

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.