## **OSRAM**

# LEDriving SLT W5W

LEDriving interior lamps for trucks



LED replacement lamp with a color temperature of up to 6,000 K

Modern and intense uniform illumination



Replaces all conventional W5W 24 V lamp bases

Easy upgrade to LED technology with plug & play solution



Reliable OSRAM quality stands for less lamp replacements

4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



### Suitable LED replacement for W5W

LEDriving SLT W5W replacement lamps offer a modern and intense light with a cool white color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional W5W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDriving SLT lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

## Product family datasheet

## Technical data

	Product information		General Informat		Electrical Data	
Product description	Application (Category and Product specific)	Product type (off- road vs. on-road)	Global o reference		Nominal voltag	e Nominal wattage
LEDriving PREMIUM SL ≜ W5W	Mainly used for signal/ indicator/ interior applications	Off-road ≙ W5W	2845DW	P	24 V	1 W
				Photometric	Data	
Dradust description	Dower input	Tost	Dower	Light color	Luminaue	Naminal

				Photometric Data		
Product description	Power input tolerance	Test voltage	Power input	Light color LED	Luminous flux tolerance	Nominal luminou s flux
LEDriving PREMIUM SL ≜ W5W	±25 %	28.0 V	0.7 W	Cool white	±25 %	65 lm

		Physical Attributes & Dimensions			
Product description	Color temperature	Diameter	Diameter	Lamp base	
LEDriving PREMIUM SL ≙ W5W	6000 K	10.1 mm	10.1 mm	W2.1x9.5d	

			Lifetime Data		
Product description	Length	Product weight	Lifespan Tc	Guarantee	Lifespan B3
LEDriving PREMIUM SL ≜ W5W	25.4 mm	1.70 g	3000 hr	4 years	1500 hr

	Capabilities	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Product description	Technology	Primary article identifier	Candidate list substance 1	CAS No. of substance 1
LEDriving PREMIUM SL ≜ W5W	LED	4062172401814	Lead	7439-92-1

Product description	Safe use instruction	Declaration no. in SCIP database
LEDriving PREMIUM SL ≜ W5W	The identification of the Candidate List substance is sufficient to allow safe use of the article.	ce57cdf7-4612-4bc6- 936c-acced2979e56

## Product family datasheet

### Download Data

	File
<b>7</b>	User instruction GPRS_Safety symbols instructions
<b>*</b>	Brochures LEDriving Retrofits - Exchange overview (EN)
乙	Brochures Sales Folder LEDriving replacement lamps (EN)

## Safety advice

Application advice: For more detailed application information and graphics please see product datasheet and user manual.

## **Application advice**

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

